


526 Rec'd PCT/PTO 06 JUL 2000 *PCT*

FORM PTO-1390 (Modified) (REV 5-93)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				065691/0196 09/582871	
		U.S. APPLICATION NO. (if known, see 37 C.F.R. 1.5) UNASSIGNED			
INTERNATIONAL APPLICATION NO. PCT/FR99/00003		INTERNATIONAL FILING DATE 05 January 1999		PRIORITY DATE CLAIMED 06 January 1998	
TITLE OF INVENTION DEVICE FOR COATING GRANULES TO BE ADMINISTERED ORALLY					
APPLICANT(S) FOR DO/EO/US Patrice DEBREGEAS, Gerard LEDUC, Pascal OURY and Patrice ROMAIN					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
1.	<input checked="" type="checkbox"/>	This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.			
2.	<input type="checkbox"/>	This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.			
3.	<input type="checkbox"/>	This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).			
4.	<input checked="" type="checkbox"/>	A proper Demand for International Preliminary Examination was made by the 19 th month from the earliest claimed priority date.			
5.	<input checked="" type="checkbox"/>	A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). <input checked="" type="checkbox"/> has been transmitted by the International Bureau. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US)			
6.	<input checked="" type="checkbox"/>	A copy of the translation of the International Application into English (35 U.S.C. 371(c)(2)).			
7.	<input checked="" type="checkbox"/>	Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). <input checked="" type="checkbox"/> have been transmitted by the International Bureau. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. <input type="checkbox"/> have not been made and will not be made.			
8.	<input checked="" type="checkbox"/>	A copy of the translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).			
9.	<input type="checkbox"/>	An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).			
10.	<input checked="" type="checkbox"/>	A copy of the translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).			
Items 11. to 16. below concern other document(s) or information included:					
11.	<input type="checkbox"/>	An Information Disclosure Statement under 37 CFR 1.97 and 1.98.			
12.	<input type="checkbox"/>	An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.			
13.	<input type="checkbox"/>	A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.			
14.	<input type="checkbox"/>	A substitute specification.			
15.	<input type="checkbox"/>	A change of power of attorney and/or address letter.			
16.	<input type="checkbox"/>	Other items or information:			

U.S. APPLICATION NO. (if known, see 37 CFR 1.53) UNASSIGNED 09/7582871		INTERNATIONAL APPLICATION NO. PCT/FR99/00003		ATTORNEY'S DOCKET NUMBER 065691/0196	
17. <input checked="" type="checkbox"/> The following fees are submitted:				CALCULATIONS PTO USE ONLY	
Basic National Fee (37 CFR 1.492(a)(1)-(5): Search Report has been prepared by the EPO or JPO \$840.00					
International preliminary examination fee paid to USPTO (37 CFR 1.482) \$670.00					
No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) \$690.00					
Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$970.00					
International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) \$96.00					
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$840.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than 20 Months from the earliest claimed priority date (37 CFR 1.492(e))					
Claims	Number Filed	Included in Basic Fee	Extra Claims	Rate	
Total Claims	19	-	20	= 0 x	\$18.00
Independent Claims	1	-	3	= 0 x	\$78.00
Multiple dependent claim(s) (if applicable)					\$260.00
TOTAL OF ABOVE CALCULATIONS =				\$840.00	
Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).				\$0.00	
SUBTOTAL =				\$840.00	
Processing fee of \$130.00 for furnishing English translation later the 20 months from the earliest claimed priority date (37 CFR 1.492(f)).				+	
TOTAL NATIONAL FEE =				\$840.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +					
TOTAL FEES ENCLOSED =				\$840.00	
				Amount to be: refunded \$	
				charged \$	
a. <input checked="" type="checkbox"/> A check in the amount of \$840.00 to cover the above fees is enclosed.					
b. <input type="checkbox"/> Please charge my Deposit Account No. <u>19-0741</u> in the amount of \$-0- to the above fees. A duplicate copy of this sheet is enclosed.					
c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>19-0741</u> . A duplicate copy of this sheet is enclosed.					
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO:					
Foley & Lardner Washington Harbour 3000 K Street, N.W., Suite 500 Washington, D.C. 20007-5109			SIGNATURE  NAME PATRICIA D. GRANADOS REGISTRATION NUMBER 33,683		

WO 99/34919

PCT/FR99/00003

534 Rec'd PCT/PTC 06 JUL 2000

DEVICE FOR COATING GRANULES TO BE ADMINISTERED ORALLY

The invention relates to the production of solid products to be administered orally, in particular pharmaceutical products such as microgranules.

Medicaments to be swallowed, formed by a gelatine capsule enclosing microgranules with a maximum dimension of, for example, between 0.4 and 1.4 mm, are known. The aim is, by means of these microgranules, to obtain steady and prolonged release over time of a substance such as an active ingredient into the organism in order to reduce the number of doses taken by the patient. The production of the microgranules involves a stage in which the active ingredient in solution is fixed around inert grains, e.g. starch. This stage should make it possible to obtain on each grain one or more uniform homogeneous coating layers of predetermined thickness formed by a solution containing the active ingredient.

An existing system makes it possible to coat tablets of dimensions greater than 5 mm. These tablets are placed in a drum having perforations of a diameter less than 5 mm in order to avoid escape of the particles while at the same time allowing air to pass through the mass of tablets to be coated. With the drum rotating, the coating liquid is atomized onto the tablets. An air circuit allows elimination of the solvents and thus continuous formation of the coating layer.

As regards the microgranules, since these generally have a diameter of between 0.4 and 1.4 mm, which is thus markedly less than that of the tablets, it is impossible to place them in this drum, because the result would be that the microgranules would immediately escape via the perforations.

To mitigate this problem, one solution, which would be very difficult to implement and costly, would be to manufacture a drum with perforations less than 0.4 mm. Moreover, the small diameter of the apertures

00500301.080900

would entail a significant pressure drop in the air circuit.

Another solution, which is less costly, is to line the inside of the drum with a metallic cloth or screen with a mesh which prevents the passage of the microgranules. In this case, there are numerous constraints:

- the fineness of the mesh makes the cloth very fragile and prone to tear, which entails the escape of the microgranules and hence the contamination of the air circuit and of the remainder of the installation;
- the mesh is very rapidly obstructed by deposition of coating residues, necessitating frequent cleaning. The risk of clogging thus makes it necessary to reduce considerably the atomization rate of the coating solution; and
- cleaning is made very difficult by the fact that the screen has to be removed. Moreover, even with thorough cleaning, there are numerous risks of contamination such that traces of a first active ingredient will be detected on the subsequent product.

One object of the invention is to provide a device suitable for the production of granules, in particular mini- or microgranules, which is easy to manufacture, entails a small pressure drop in the air circuit, reduces the risks that the product will escape into the installation, reduces the risks of cross-contamination and allows fixing or coating with a high output of coating or fixing substance.

With a view to achieving this object, the invention provides a device for the production of granules, in particular pharmaceutical granules, the device having a drum with peripheral apertures and a member for feeding the drum with coating or fixing substance, in which the drum has mutually parallel sections which define between them the apertures.

The width of the apertures thus depends on the spacing chosen for the sections. This spacing can be

005030 T 2023560

very small so as to obtain very narrow apertures suitable for the production of microgranules with a diameter between 0.4 and 1.5 mm, for example. This drum is easy to manufacture, including very narrow apertures. Moreover, the percentage of gaps in the wall of the drum is high, such that the pressure drop as any circulating air crosses the drum is reduced. The sections make the wall of the drum very strong. Any risk that the granules will escape into the installation is thus avoided. The sections are very easy to clean, in particular from the outside of the drum, thus reducing the risks of cross-contamination when fixing two different products in succession. Moreover, since the sections cause little clogging, fixing or coating can be carried out at a high rate of flow of coating or fixing fluid. Hence, when the products to be fixed or coated are sensitive to heat or humidity, the risks of degradation of the products are avoided. The device is particularly suitable for fixing or coating microgranules for medical applications comprising an active ingredient which should be released steadily and over a prolonged period into the organism.

It is advantageous if the sections have edges arranged opposite one another.

The edges thus make it possible to define the dimensions of the apertures very accurately.

It is advantageous if the edges delimit a flat face of each section, the said face facing the inside of the drum.

The flat faces of the sections thus define a flat internal face of the drum, which may be cylindrical, allowing the products fixed or coated to be given a very smooth surface.

It is advantageous if each section has a width that decreases from the inside towards the outside of the drum.

09582871-000000

The drum is thus simple to clean, particularly from the outside of the drum, the lateral faces of the sections guiding a cleaning fluid towards the apertures between the sections for the purpose of unclogging them.

It is advantageous if each section has a triangular profile.

It is advantageous if the sections are rectilinear and parallel to an axis of rotation of the drum.

It is advantageous if the sections are curved.

It is advantageous if the drum has sectors which carry the sections and can be removed independently of one another.

This makes the drum easier to clean.

It is advantageous if the substance feed member is arranged in the drum.

It is advantageous if the substance feed member comprises an atomizer.

It is advantageous if the substance feed member is connected to a source of liquid.

It is advantageous if the substance feed member is connected to a source of compressed air.

It is advantageous if the device has means for the continuous supply of a gas to the interior of the drum and for forcing the gas to pass through the apertures from the inside towards the outside of the drum.

It is advantageous if the device has means for heating the gas upstream of the drum.

It is advantageous if the device is set up such that the gas passes through the apertures from the outside towards the inside of the drum.

The invention also provides a process for producing granules, in particular pharmaceutical granules, in which use is made of a device according to the invention.

006030" T 2828550

Moreover, the invention provides granules, in particular pharmaceutical granules, which have been produced by means of a process according to the invention.

5 The invention also provides packaging such as a sachet or gelatine capsule comprising granules according to the invention.

Other characteristics and advantages of the invention will become apparent from the following description of a preferred embodiment given by way of nonlimitative example. In the attached drawings:

- Figure 1 is a schematic view showing the circulation of the fluids in a device according to a preferred embodiment of the invention;
- 15 - Figure 2 is a perspective view of the drum of the device in Figure 1 with a wall sector removed;
- Figure 3 is a perspective view of part of the wall of the drum in Figure 2;
- Figure 4 is a view in cross section in the plane
20 IV-IV of the wall in Figure 3; and
- Figure 5 is a view similar to Figure 2 showing a variant embodiment of the drum.

Referring to Figure 1, in a preferred embodiment the fixing or coating device according to 25 the invention comprises an enclosure 2 containing a drum or turbine 4.

The drum 4 has a cylindrical peripheral wall 6 with an axis 8 and two frustoconical end walls 10 extending at two respective end edges of the cylindrical wall 6 and tapering away from these edges. The drum 4 has two cylindrical bearings 11 fixed to the narrower edges of the end walls 10. One of the bearings 11 is hollow and the other is solid. The cylindrical wall 6 has apertures 12 in the form of sectors of a cylinder. The drum 4 furthermore comprises wall elements 14 having the form of a sector of a cylinder complementary to that of the apertures 12. Each element 14 comprises a frame 16 having two mutually parallel

rectilinear edges 18 and two circular edges 20 and capable of being fixed in a removable manner on the wall 6 to close the associated aperture 11.

The wall element 14 has metallic sections 22, each identical to the other. Each section 22 is rectilinear and here has the general profile of an isosceles triangle. That angle of the triangle which is associated with the two equal sides is rounded, while the two other angles define sharp edges 23 of the section. The section thus has two mutually identical flat lateral faces 24 contiguous to the rounded angle and one flat front face 26 opposite this angle, the face 26 being delimited by the two sharp edges 23, between these two edges. Each section 22 has a width which decreases from the inside towards the outside of the drum 4. The sections 22 are spaced apart, face one another and extend parallel to one another and to the rectilinear edges 18 of the frame. The flat front faces 26 are substantially coplanar to one another. They are arranged in such a way as to define, perpendicularly to the sections 22, a discontinuous cylindrical internal face with a curvature identical to that of the curved edges 20 of the frame 16. The rounded edges of the sections 22 are all turned towards the outside on the side opposite the centre of curvature. The sharp edges 23 of the adjacent sections 22 extend parallel to one another, facing one another and at a distance from one another in such a way that they define between them apertures 25 in the form of rectilinear slits parallel to the axis 8. The spacing between the edges 23 is indicated by d in Figure 4. The ends of the sections 22 are fixed to the curved edges 20 of the frame 16. The wall element 14 can advantageously have section supports 28 of flat curved form extending at a distance from one another in planes perpendicular to the axis of the cylindrical face defined by the front faces 26. The ends of the supports 28 are fixed to the rectilinear edges 18 of the frame. They are fixed to the sections

09582871.000000

22 on the outside, opposite the front faces 26, by means of a part 29 with a pointed profile of the supports 28. These supports prevent the deformation of the rectilinear sections 22 and keep the distance d
5 constant along the entire length of the sections.

The removable wall elements 14 can be cleaned easily from the outside. The opposing lateral faces 24 guide a cleaning fluid towards the apertures 25 in order to unclog them.

10 In the device 2, the drum 4 can rotate about its axis 8 and is driven in rotation about this axis by suitable means. The enclosure 2 has a port facing one of the bearings 11 to allow the introduction of grains 44 into the drum 4 via this bearing.

15 The device has an atomizer 30 capable of being simultaneously in fluid communication with a source of compressed air 32 and a liquid pump 34. This liquid is a coating solution and comprises, for example, an excipient solvent and an active ingredient dissolved in
20 the solvent. The atomizer 30 extends in the drum 2 opposite the cylindrical internal face, the feed conduits of the atomizer 30 passing through the hollow bearing 11. The drum 4 has helical blades 31 fixed to the internal wall of the drum to accentuate the
25 rotation of the grains 44 in the drum.

The device has an air feed conduit 36 opening into the enclosure 2 and means 38 extending in the conduit 36 upstream of the enclosure 2 for lowering or increasing the temperature of the air fed into the
30 enclosure and moreover for regulating the humidity of this air. The device has an air outlet opening 40 contiguous to the cylindrical wall of the drum 4 and communicating with an air exhaust conduit 42 extending outside the enclosure. The opening 40 is arranged
35 opposite a lower lateral part of the drum 4 where the grains 44 accumulate during the rotation of the drum. The atomizer 30 is aligned in such a way as to discharge the coating or fixing fluid 45 in the

006080" 4228550

To implement the process according to the invention, a specific quantity of grains 44 to be fixed or coated or of microgranules already partially fixed or coated is introduced into the drum 4 via the port. 15 The distance d is chosen to be less than a minimum diameter of these grains in order to prevent them from escaping via the cylindrical wall. The drum 4 is then set in rotation. The air circuit 36, 42 is put into operation, followed by the atomizer 30 for feeding the 20 drum with a coating solution containing, for example, an active ingredient. To this end, the air supplied via the conduit 36 passes radially through the apertures 25 between the sections 22 in order to pass from the outside towards the inside of the drum 4. The air then 25 passes through a fraction of the mass of grains 44 in rotation, then entrains the solvent radially through the apertures 25, this time from the inside towards the outside of the drum, and through the opening 40 towards the exhaust conduit 42. The active ingredient 30 accumulates progressively on the grains 44 while the solvent is entrained and discharged into the conduit 42 by the air.

In the variant shown in Figure 5, the drum 4 does not have a removable wall element: the sections 22 and, if appropriate, their supports 28, form the cylindrical wall themselves.

The device according to the invention can be used for fixing or coating products to be taken orally

Figure 1 consists of seven vertically stacked line graphs, labeled (a) through (g), showing the time course of various physiological parameters during a 10-minute rest period. The x-axis for all graphs is 'Time (min)' ranging from 0 to 10. The y-axis for each graph represents a different parameter. The data is categorized into three groups: Control (open circles), 100 mg/kg (filled circles), and 200 mg/kg (open squares). Error bars represent standard error of the mean (SEM).

- (a) HR (b/min): The y-axis ranges from 60 to 120. All groups show a slight increase in heart rate over time, with the 200 mg/kg group showing the highest values.
- (b) SBP (mmHg): The y-axis ranges from 100 to 140. All groups show a slight increase in systolic blood pressure over time, with the 200 mg/kg group showing the highest values.
- (c) DBP (mmHg): The y-axis ranges from 60 to 100. All groups show a slight increase in diastolic blood pressure over time, with the 200 mg/kg group showing the highest values.
- (d) MAP (mmHg): The y-axis ranges from 60 to 100. All groups show a slight increase in mean arterial pressure over time, with the 200 mg/kg group showing the highest values.
- (e) SV (L/min): The y-axis ranges from 0 to 10. All groups show a slight increase in stroke volume over time, with the 200 mg/kg group showing the highest values.
- (f) CO (L/min): The y-axis ranges from 0 to 10. All groups show a slight increase in cardiac output over time, with the 200 mg/kg group showing the highest values.
- (g) SVI (ml/m²): The y-axis ranges from 0 to 10. All groups show a slight increase in stroke volume index over time, with the 200 mg/kg group showing the highest values.

such as tablets or microgranules to be divided up into doses and enclosed in gelatine capsules or sachets. These products can be used for medical, therapeutic or cosmetic applications or be used as dietary supplements.

Of course, numerous modifications can be made to the invention without departing from the scope of the latter. The sections which define the apertures 25 between them could be curved and inclined relative to the axis 8 of the drum, being, for example, included in planes perpendicular to this axis.

The sections can have a profile of a different form, e.g. trapezoidal or in the form of a half disc.

[illegible]

CLAIMS

- 5 1. Device for the production of granules, in particular pharmaceutical granules, the device having a drum (4) with peripheral apertures (25) and a member (30) for feeding the drum with coating or fixing substance, characterized in that the drum (4) has
10 mutually parallel sections (22) which define between them the apertures (25).
2. Device according to Claim 1, characterized in that the sections (22) have edges (23) arranged opposite one another.
- 15 3. Device according to Claim 2, characterized in that the edges (23) delimit a flat face (26) of each section (22), the said face facing the inside of the drum (4).
4. Device according to any of Claims 1 to 3,
20 characterized in that each section (22) has a width which decreases from the inside towards the outside of the drum.
5. Device according to any of Claims 1 to 4, characterized in that each section (22) has a
25 triangular profile.
6. Device according to any of Claims 1 to 5, characterized in that the sections (22) are rectilinear and parallel to an axis (8) of rotation of the drum.
7. Device according to any of Claims 1 to 5,
30 characterized in that the sections are curved.
8. Device according to any of Claims 1 to 7, characterized in that the drum (4) has sectors (12) which carry the sections (22) and can be removed independently of one another.
- 35 9. Device according to any of Claims 1 to 8, characterized in that the substance feed member (30) is arranged in the drum (4).

006080 1 080900

10. Device according to any of Claims 1 to 9, characterized in that the substance feed member (30) comprises an atomizer.

11. Device according to any of Claims 1 to 10,
5 characterized in that the substance feed member (30) is connected to a source of liquid (34).

12. Device according to any of Claims 1 to 11, characterized in that the substance feed member (30) is connected to a source of compressed air (32).

10 13. Device according to any of Claims 1 to 12, characterized in that it has means (36, 42) for the continuous supply of a gas to the interior of the drum (4) and for forcing the gas to pass through the apertures (25) from the inside towards the outside of
15 the drum (4).

14. Device according to Claims 13, characterized in that it has means (38) for modifying the temperature of the gas upstream of the drum (4).

15. Device according to Claim 13 or 14,
20 characterized in that it is set up such that the gas passes through the apertures (25) from the outside towards the inside of the drum (4).

16. Process for producing granules, in particular pharmaceutical granules, characterized in that use is
25 made of a device according to one of Claims 1 to 15.

17. Granules, in particular pharmaceutical granules, characterized in that they have been produced by means of a process according to Claim 16.

18. Packaging such as a sachet or gelatine capsule,
30 characterized in that it comprises granules according to Claim 17.

006080" T2828560

CLAIMS

- 5 1. Device for the production of granules, in particular pharmaceutical granules, the device having a drum (4) with peripheral apertures (25) and a member (30) for feeding the drum with coating or fixing substance, characterized in that the drum (4) has
- 10 mutually parallel sections (22) which define between them the apertures (25).
2. Device according to Claim 1, characterized in that the sections (22) have edges (23) arranged opposite one another.
- 15 3. Device according to Claim 2, characterized in that the edges (23) delimit a flat face (26) of each section (22), the said face facing the inside of the drum (4).
4. Device according to any of Claims 1 to 3,
- 20 characterized in that each section (22) has a width which decreases from the inside towards the outside of the drum.
5. Device according to any of Claims 1 to 4, characterized in that each section (22) has a
- 25 triangular profile.
6. Device according to any of Claims 1 to 5, characterized in that the sections (22) are rectilinear and parallel to an axis (8) of rotation of the drum.
7. Device according to any of Claims 1 to 5,
- 30 characterized in that the sections are curved.
8. Device according to any of Claims 1 to 7, characterized in that the drum (4) has sectors (12) which carry the sections (22) and can be removed independently of one another.
- 35 9. Device according to any of Claims 1 to 8, characterized in that the substance feed member (30) is arranged in the drum (4).

10. Device according to any of Claims 1 to 9, characterized in that the substance feed member (30) comprises an atomizer.

11. Device according to any of Claims 1 to 10,
5 characterized in that the substance feed member (30) is connected to a source of liquid (34).

12. Device according to any of Claims 1 to 11, characterized in that the substance feed member (30) is connected to a source of compressed air (32).

10 13. Device according to any of Claims 1 to 12, characterized in that it has means (36, 42) for the continuous supply of a gas to the interior of the drum (4) and for forcing the gas to pass through the apertures (25) from the inside towards the outside of
15 the drum (4).

14. Device according to Claims 13, characterized in that it has means (38) for modifying the temperature of the gas upstream of the drum (4).

15. Device according to Claim 13 or 14,
20 characterized in that it is set up such that the gas passes through the apertures (25) from the outside towards the inside of the drum (4).

16. Process for producing granules, in particular pharmaceutical granules, characterized in that use is
25 made of a device according to one of Claims 1 to 15.

17. Granules, in particular pharmaceutical granules, characterized in that they have been produced by means of a process according to Claim 16.

18. Packaging such as a sachet or gelatine capsule,
30 characterized in that it comprises granules according to Claim 17.




FIG. 5

[illegible]




FIG. 2




FIG. 3




FIG. 4

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

DEVICE FOR COATING GANULES TO BE ADMINISTERED ORALLY

the specification of which is attached hereto unless the following box is checked:

☒ was filed on JANUARY 5, 1999 as ~~United States Application Number~~ or PCT International Application Number PCT/FR99/00003 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is known by me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

NUMBER	COUNTRY	DAY/MONTH/YEAR FILED	PRIORITY CLAIMED
98/00048	FRANCE	06/JANUARY/1998	YES

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

APPLICATION NO.	FILING DATE


I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is known by me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:


APPLICATION SERIAL NO.	FILING DATE	STATUS: PATENTED, PENDING, ABANDONED


19 I hereby appoint as my attorneys, with full powers of substitution and revocation, to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Stephen A. Bent, Reg. No. 29,768; David A. Blumenthal, Reg. No. 26,257; William T. Ellis, Reg. No. 26,874; John J. Feldhaus, Reg. No. 28,822; Patricia D. Granados, Reg. No. 33,683; John P. Isacson, Reg. No. 33,715; Donald D. Jeffery, Reg. No. 19,980; Eugene M. Lee, Reg. No. 32,039; Richard Linn, Reg. No. 25,144; Peter G. Mack, Reg. No. 26,001; Brian J. McNamara, Reg. No. 32,789; Sybil Meloy, Reg. No. 22,749; George E. Quillin, Reg. No. 32,792; Colin G. Sandercock, Reg. No. 31,298; Bernhard D. Saxe, Reg. No. 28,665; Charles F. Schill, Reg. No. 27,590; Richard L. Schwaab, Reg. No. 25,479; Arthur Schwartz, Reg. No. 22,115; Harold C. Wegner, Reg. No. 25,258.


Address all correspondence to FOLEY & LARDNER, Washington Harbour, 3000 K Street, N.W., Suite 500, P.O. Box 25696, Washington, D.C. 20007-8696. Address telephone communications to Patricia D. Granados at (202) 672-5300.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1-00 Full Name of First or Sole Inventor <u>DEBREGEAS Patrice</u>	Signature of First or Sole Inventor 	Date July 4, 2000
Residence Address 30 rue des Saints Pères, 75007 <u>PARIS</u> , FRANCE FRX	Country of Citizenship FRANCE	
Post Office Address The same as residence		

2-00 Full Name of Second Inventor <u>LEDUC Gérard</u>	Signature of Second Inventor 	Date July 4, 2000
Residence Address La Grange, Labrosse, 45330 <u>MALESHERBES</u> , FRANCE FRX	Country of Citizenship FRANCE	
Post Office Address The same as residence		

3-00 Full Name of Third Inventor <u>OURY Pascal</u>	Signature of Third Inventor 	Date July 4, 2000
Residence Address 16 rue Montbauron, 78100 <u>VERSAILLES</u> , FRANCE FRX	Country of Citizenship FRANCE	
Post Office Address The same as residence		

4-00 Full Name of Fourth Inventor <u>ROMAIN Patrice</u>	Signature of Fourth Inventor 	Date July 4, 2000
Residence Address 11 rue du Tilleul, 76000 <u>ROUEN</u> , FRANCE FRX	Country of Citizenship FRANCE	
Post Office Address The same as residence		

Full Name of Fifth Inventor	Signature of Fifth Inventor	Date
Residence Address	Country of Citizenship	
Post Office Address		